

SOLUTIONS FOR ENERGY SAVINGS

# Polyethylene Seam Tape

Self-adhering tape specifically engineered to seal end joints and longitudinal seams of PE pipe insulation.

- // Low profile tape for covering seams
- // Provides extra protection on seams
- // Creates a clean visual appearance
- // 1.88 inches (48 mm) x 180 feet (55 m) x 3 mil

[www.armacell.us](http://www.armacell.us)



 **armacell**<sup>®</sup>  
ArmaLight<sup>®</sup>

## TECHNICAL DATA - POLYETHYLENE SEAM TAPE

<b>Brief description</b>	Black bi-axially oriented polypropylene tape coated with a cold weather solvent acrylic adhesive. For use on domestic hot/cold water and plumbing applications only. Compatible with Tubolit, Tundra and Imcoa pipe insulation.
<b>Specifications</b>	
<b>Color</b>	Glossy Black
<b>Width</b>	1.88" (48mm)
<b>Length</b>	180 feet (55 m)
<b>Container</b>	Sold 24 rolls per carton
<b>Storage</b>	Store in a clean, dry place. Temperature of 40° to 80° F (4° - 26° C) and 40 to 50% relative humidity are recommended.
<b>Shelf Life</b>	To obtain best performance, use this product within 12 months from date of manufacture.
<b>Flame and Smoke Rating</b>	0/0 per UL 723
<b>Service temperature</b>	40° F to 180° F
<b>Part Number</b>	IPTAP003260

#### Application Notes:

- Pre-cut strips to size to allow a 2" overlap on the circumference.
- The tape must be centered over the seam.
- Apply firm pressure on entire length and width of the taped surface. This is to ensure proper adhesion.
- Do not over tighten. Taped seam should not compress the foam insulation.

All data and technical information are based on results achieved under the specific conditions defined according to the testing standards referenced. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. Measurements in the product tables may offer minimal variances which do not significantly affect the product recommendation and/or performance. Armacell takes every precaution to ensure the accuracy of the data provided in this document and all statements, technical information and recommendations contained within are believed to be correct at the time of publication. By ordering/receiving product you accept the **Armacell General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received these.

© Armacell, 2020. Tubolit, Tundra and Imcoa are trademarks of the Armacell Group

00400 | PE Seam Tape | ArmaLight | TDS | 092020 | NA | E-NA

## ABOUT ARMACELL

As the inventors of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal, acoustic and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With 3,100 employees and 24 production plants in 16 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for high-tech and lightweight applications and next generation aerogel blanket technology.

For more information, please visit:

[www.armacell.us](http://www.armacell.us)

800-866-5638

