

OleTex®



# POLYOLEFIN COMPONENT FOAM GASKETS AND SEALS FOR OEM MARKETS



- Wide range of polyolefin foam materials
- Cross-linked polyethylene in roll or bun (block) form

 **armacell**®

Engineered For Success.

Product Name (OleTex®)	Density (lb/ft <sup>3</sup> )	Tensile Strength (psi)	Elongation (%)	25% Compression Deflection (psi)	Polymer Type and Form Available
CKJN 200	2.0	44	115	6.8	LDPE - Rolls
CKJN 300	3.0	70	135	9.6	LDPE - Rolls
CKJN 400	4.0	97	150	13	LDPE - Rolls
CKJN 600	6.0	145	175	24	LDPE - Rolls
CKJN 800	8.0	190	190	36	LDPE - Rolls
CKJN 1000	10.0	225	195	50	LDPE - Rolls
CKJN 1200	12.0	265	210	67	LDPE - Rolls
CKJN 1600	16.0	370	230	90	LDPE - Rolls
CKJN 2000	20.0	450	240	140	LDPE - Rolls
CKJN 3000	30.0	620	240	310	LDPE - Rolls
CDJN 200	2.0	46	210	6.2	LDPE/EVA - Rolls
CDJN 300	3.0	70	225	7.4	LDPE/EVA - Rolls
CDJN 400	4.0	95	235	10	LDPE/EVA - Rolls
CDJN 440	4.4	100	235	11	LDPE/EVA - Rolls
CAJN 200	2.0	28	230	5.3	EEA - Rolls
CSJN 600	6.0	140	130	31	Stiff/Proprietary - Rolls
BKJN 200	2.0	46	140	8.1	LDPE - Buns
BKJN 300	3.0	71	155	15	LDPE - Buns
BKJN 400	4.0	94	185	23	LDPE - Buns
BCJN 200	2.0	43	170	6.9	LDPE/EVA - Buns
BDJN 200	2.0	49	190	6.5	LDPE/EVA - Buns
BDJN 300	3.0	76	255	11	LDPE/EVA - Buns
BDJN 400	4.0	92	305	14	LDPE/EVA - Buns
BSJN 200	2.0	40	130	9	Stiff/Proprietary - Buns
BSJN 300	3.0	60	150	19	Stiff/Proprietary - Buns
BSJN 400	4.0	82	190	29	Stiff/Proprietary - Buns

Roll goods available from 2 lbs/ft<sup>3</sup> up to 30 lbs/ft<sup>3</sup>.

Roll thickness range from 1/8" to 7/8", and up to 3" laminated.

Roll widths available from 6" up to 88".

Bun Sizes are 4" x 48" x 72" and 4" x 60" x 72".

Custom densities, thicknesses and formulations are available upon request.

Testing performed to ASTM D3575. Values listed are typical, and do not warrant or imply a specification.

## Why Armacell?

Armacell is the global leader in expanded cellular foam products delivering decades of product knowledge and innovation to our partners in the automotive, heavy equipment, transportation, industrial and construction markets.

### ARMACELL LLC

TEL: 800.866.5638

or 919.304-3846 ext 3972

FAX: 919.304.3847

info.us@armacell.com

www.armacell.us

7600 Oakwood Street Extension, Mebane, NC 27302



Armacell provides this information as a technical service. To the extent the information is derived from sources other than Armacell, Armacell is substantially, if not wholly, relying upon the other source(s) to provide accurate information. Information provided as a result of Armacell's own technical analysis and testing is accurate to the extent of our knowledge and ability, as of date of printing, using effective standardized methods and procedures. Each user of these products, or information, should perform their own tests to determine the safety, fitness and suitability of the products, or combination of products, for any foreseeable purposes, applications and uses by the user and by any third party to which the user may convey the products. Since Armacell cannot control the end use of this product, Armacell does not guarantee that the user will obtain the same results as published in this document. The data and information are provided as a technical service and are subject to change without notice.