

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Armaflex Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

designed for cleaning surfaces/substrates before applying Armaflex glues and cleaning tools (except Armaflex SF990 and Armaflex Ultima SF990)

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Armacell GmbH
Robert-Bosch-Straße 10
48153 Münster

Telephone no. +49 (0) 251 - 7603-200

Fax no. +49 (0) 251 - 7603-561

e-mail info.de@armacell.com

Information provided by / telephone

Dr. Heribert Quante, Tel.: +49 (0) 251 - 7603-227

Advice on Safety Data Sheet

heribert.quante@armacell.com

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412

Eye Irrit. 2; H319

Flam. Liq. 2; H225

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

ethyl-acetate

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P391 Collect spillage.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

Supplemental label elements

Regulation (EC) No 648/2004 on detergents (Annex VII):
 5-<15 % Aliphatic hydrocarbons

2.3 Other hazards

Vapours can form an explosive mixture with air.

PBT assessment
 No data available.

vPvB assessment
 No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	ethyl-acetate			
	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 70.00 - < 90.00	%-b.w.
2	butanone			
	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 10.00 - < 25.00	%-b.w.
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			
	64742-49-0 926-605-8 - 01-2119486291-36	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 2; H225 STOT SE 3; H336	>= 5.00 - < 10.00	%-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

When inhaled remove to fresh air and seek medical aid.

After skin contact

When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Seek medical advice immediately.

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Irritating to eyes, respiratory system and skin. breath difficulties; Coughing; Dizziness; Dizziness; Headache; Nausea; reddening of the skin; blistering

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet; Carbon dioxide; Dry chemical extinguisher; Foam

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Do not inhale vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. In case of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up rest with absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). When picked up, treat material as prescribed under heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary).

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - refrain from smoking. Take precautionary measures against static charges.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage.

Advice on storage assembly

Do not store together with: explosive substances; spontaneously combusting substances

7.3 Specific end use(s)

No data available.

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	2017/164/EU		
	Ethyl acetate		
	WEL short-term (15 min reference period)	1468	mg/m ³ 400 ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m ³ 200 ppm
List of approved workplace exposure limits (WELs) / EH40			
	Ethyl acetate		
	WEL short-term (15 min reference period)		400 ppm
	WEL long-term (8-hr TWA reference period)		200 ppm
2	butanone	78-93-3	201-159-0
	2000/39/EC		
	Butanone		
	WEL short-term (15 min reference period)	900	mg/m ³ 300 ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m ³ 200 ppm
List of approved workplace exposure limits (WELs) / EH40			
	Butan-2-one		
	WEL short-term (15 min reference period)	899	mg/m ³ 300 ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m ³ 200 ppm
	Comments	Sk, BMGV	
3	n-hexane	110-54-3	203-777-6
	2006/15/EC		
	n-Hexane		
	WEL long-term (8-hr TWA reference period)	72	mg/m ³ 20 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	n-Hexane		
	WEL long-term (8-hr TWA reference period)	72	mg/m ³ 20 ppm
4	cyclohexane	110-82-7	203-806-2
	2006/15/EC		
	Cyclohexane		
	WEL long-term (8-hr TWA reference period)	700	mg/m ³ 200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Cyclohexane		
	WEL short-term (15 min reference period)	1050	mg/m ³ 300 ppm
	WEL long-term (8-hr TWA reference period)	350	mg/m ³ 100 ppm

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethyl-acetate			141-78-6 205-500-4	
	dermal	Long term (chronic)	systemic	63	mg/kg/day
	inhalative	Short term (acute)	systemic	1468	mg/m ³
	inhalative	Long term (chronic)	local	734	mg/m ³
	inhalative	Short term (acute)	local	1468	mg/m ³
	inhalative	Long term (chronic)	systemic	734	mg/m ³
2	butanone			78-93-3 201-159-0	
	dermal	Long term (chronic)	systemic	1161.00	mg/kg/day
	inhalative	Long term (chronic)	systemic	600.00	mg/m ³
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			64742-49-0 926-605-8	
	dermal	Long term (chronic)	systemic	773	mg/kg/day
	inhalative	Long term (chronic)	systemic	2035	mg/m ³

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	ethyl-acetate			141-78-6 205-500-4	
	oral	Long term (chronic)	systemic	4.5	mg/kg/day
	dermal	Long term (chronic)	systemic	37	mg/kg/day
	inhalative	Short term (acute)	systemic	734	mg/m ³
	inhalative	Long term (chronic)	local	367	mg/m ³
	inhalative	Short term (acute)	local	734	mg/m ³
	inhalative	Long term (chronic)	systemic	367	mg/m ³
2	butanone			78-93-3 201-159-0	
	oral	Long term (chronic)	systemic	31.00	mg/kg/day
	dermal	Long term (chronic)	systemic	412.00	mg/kg/day
	inhalative	Long term (chronic)	systemic	106.00	mg/m ³
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			64742-49-0 926-605-8	
	oral	Long term (chronic)	systemic	699	mg/kg/day
	dermal	Long term (chronic)	systemic	699	mg/kg/day
	inhalative	Long term (chronic)	systemic	603	mg/m ³

PNEC values

No	Substance name		CAS / EC no		
	ecological compartment	Type	Value		
1	ethyl-acetate		141-78-6 205-500-4		
	water	fresh water	0.24	mg/L	
	water	marine water	0.024	mg/L	
	water	Aqua intermittent	1.65	mg/L	
	water	fresh water sediment	1.15	mg/kg dry weight	
	water	marine water sediment	0.115	mg/kg dry weight	
	soil	-	0.148	mg/kg dry weight	
	sewage treatment plant	-	650	mg/L	
	secondary poisoning	-	200	mg/kg	
	2	butanone		78-93-3 201-159-0	
		water	fresh water	55.80	mg/L
water		marine water	55.80	mg/L	
water		Aqua intermittent	55.8	mg/L	
water		fresh water sediment	284.74	mg/kg	
with reference to: dry weight					
water		marine water sediment	284.7	mg/kg	
with reference to: dry weight					
soil		-	22.5	mg/kg	
with reference to: dry weight					
sewage treatment plant		-	709	mg/L	
secondary poisoning	-	1000	mg/kg		
with reference to: food					

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of insufficient ventilation and during spray application respiratory protection necessary. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator

A-P2

Eye / face protection

Safety glasses with side protection shield (EN 166)

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection:		
Appropriate Material	chloroprene		
Appropriate Material	nitrile rubber		
Appropriate Material	PVA		
Material thickness	min.	0.75	mm
Breakthrough time	30	- 120	min

Other

Chemical-resistant work clothes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour			
liquid			
clear			
Odour			
of solvents			
Odour threshold			
No data available			
pH value			
No data available			
Boiling point / boiling range			
Value	appr.	70	°C
Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
Value	appr.	-20	°C
Auto-ignition temperature			
No data available			
Oxidising properties			
No data available			
Explosive properties			
No data available			
Flammability (solid, gas)			
No data available			
Lower flammability or explosive limits			
Value		1	% vol
Upper flammability or explosive limits			
Value		13	% vol
Vapour pressure			
Value	<	1100	hPa
Reference temperature		50	°C

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

Vapour density			
No data available			
Evaporation rate			
No data available			
Relative density			
No data available			
Density			
Value	appr.	0.9	g/cm ³
Reference temperature		20	°C
Solubility in water			
No data available			
Solubility(ies)			
No data available			
Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	log Pow		6.8
	Reference temperature		25 °C
	Source	ECHA	
2	butanone	78-93-3	201-159-0
	log Pow		0.3
	Reference temperature		40 °C
	Method	OECD 117	
	Source	ECHA	
Viscosity			
Value	<	21	cSt
Reference temperature		40	°C

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

None, if handled according to order.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

None, if handled according to intended use.

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LD50	>	5600	mg/kg bodyweight
Species	rat		
Source	ECHA		
2	butanone	78-93-3	201-159-0
LD50	>	3460	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LD50	>	20000	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
2	butanone	78-93-3	201-159-0
LD50	>	10	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
LC50	>	25.2	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	low-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	butanone	78-93-3	201-159-0
Duration of exposure		4	h
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	irritant		

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	Species	rabbit	
	Method	OECD 405	
	Source	ECHA	
	Evaluation	low-irritant	
2	butanone	78-93-3	201-159-0
	Species	rabbit	
	Method	OECD 405	
	Source	ECHA	
	Evaluation	irritant	
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	Route of exposure	Skin	
	Species	guinea pig	
	Method	OECD 406	
	Source	ECHA	
	Evaluation	non-sensitizing	
2	butanone	78-93-3	201-159-0
	Route of exposure	Skin	
	Species	guinea pig	
	Method	OECD 406	
	Source	ECHA	
	Evaluation	non-sensitizing	
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
	Species	Salmonella typhimurium	
	Method	OECD 471	
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
2	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
	Route of exposure	inhalational	
	Type of examination	Chromosome aberration test	
	Species	rat	
	Method	OECD 475	
	Source	ECHA	
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
	Route of exposure	inhalational	
	NOAEC	9000	ppm
	Type of examination	2 generation study	
	Species	rat	
	Method	OECD 416	
	Source	ECHA	
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
	Route of exposure	inhalational	
	NOAEC	3000	ppm
	Species	rat	
	Method	OECD 451	
	Source	ECHA	

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

STOT - single exposure			
No data available			
STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
Route of exposure		inhalational	
NOAEC		14000	mg/m ³
Duration of exposure		8	h
Species		rat	
Source		ECHA	
Aspiration hazard			
No data available			
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Inhalation of the vapours causes irritation of the respiratory tract and mucous membrane, headaches, nausea, giddiners, vomiting.			

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LC50		230	mg/l
Duration of exposure		96	h
Species		Pimephales promelas	
Source		ECHA	
2	butanone	78-93-3	201-159-0
LC50		2993	mg/l
Duration of exposure		96	h
Species		Pimephales promelas	
Method		OECD 203	
Source		ECHA	
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
LL50		11.4	mg/l
Duration of exposure		96	h
Species		Oncorhynchus mykiss	
Method		OECD 203	
Source		ECHA	
Toxicity to fish (chronic)			
No data available			
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
EC50		1350	mg/l
Duration of exposure		48	h
Species		Daphnia magna	
Source		ECHA	
2	butanone	78-93-3	201-159-0
EC50		308	mg/l
Duration of exposure		48	h
Species		Daphnia magna	
Method		OECD 202	
Source		ECHA	
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
EL50		3	mg/l
Duration of exposure		48	h
Species		Daphnia magna	
Method		OECD 202	
Source		ECHA	

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

Toxicity to Daphnia (chronic)			
No data available			

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	butanone	78-93-3	201-159-0
EC50		2029	mg/l
Duration of exposure		96	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
2	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
EL50		1030	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No data available			

Bacteria toxicity			
No data available			

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Source	ECHA		
Evaluation	readily biodegradable		
2	butanone	78-93-3	201-159-0
Type	aerobic biodegradation		
Value		98	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
3	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
Type	aerobic biodegradation		
Value		98	%
Duration		28	day(s)
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily degradable		

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
log Pow		6.8	
Reference temperature		25	°C
Source	ECHA		
2	butanone	78-93-3	201-159-0
log Pow		0.3	
Reference temperature		40	°C
Method	OECD 117		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Do not discharge product unmonitored into the environment.
Do not discharge into the drains or waters and do not store on public depositories.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	ethyl-acetate butanone
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	ethyl-acetate butanone
EmS	F-E, S-E
Label	3

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Technical name	ethyl-acetate butanone
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

Trade name: Armaflex Cleaner

Current version : 2.3.0, issued: 04.01.2019

Replaced version: 2.2.1, issued: 24.10.2017

Region: GB

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 3, 40
---	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content	870 g/l
-------------	---------

15.2 Chemical safety assessment

No data available.

SECTION 16: Other information

Further information

Authors responsible for the compilation of the material safety data sheet: UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de.

The information is based on our current knowledge however it does not represent a guarantee of product properties nor does it create any legal obligation.

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 636648