

PROTECTION INDOORS AND OUT

ArmaFlex WB Finish

ArmaFlex® WB Finish is the durable, white, protective finish formulated for use over all ArmaFlex insulations for protection against ultraviolet radiation, weather and ozone damage or where a clean, white aesthetic is desired.

- // Suitable for both indoor and outdoor applications.
- // Provides a clean, white, protective finish which guards against UV and ozone damage.
- // Formulated for cold weather flexibility to resist cracking.
- // Water-based, 100% acrylic is fast drying without solvent fumes. Cleans up with soap and water.
- // Outdoor surfaces should be recoated every 2-4 years.

www.armacell.us



 **armacell**[®]
ArmaFlex[®]

TECHNICAL DATA – ARMAFLEX® WB FINISH

Description

White, water-based, 100% acrylic coating

Typical Properties

Physical Properties	Value
Color:	Available in Standard White. Tinting possible for indoor use only. No tinting for outdoor applications.
Net Weight:	11.3 lbs. per gallon (1.35 kg/l)
Composition:	Pigmented latex V.O.C. Less than 50 g/l (calculated)
Solid Content:	Approximately 65% by weight and 53% by volume.
Viscosity:	95 - 120 KU
Application:	Brush or roller. Apply at temperatures above 50°F (10°C) and when no freezing temperatures are expected for 24 hours
Coverage:	200 - 400 sq. ft. (37 sq.m.) per gallon per single brush coat, depending on temperature and substrate.
Shelf Life:	One year in original sealed container. Storage temperature 60° to 80°F (16° to 27°C). Keep from freezing.
Minimum Drying Time:	Four hours minimum for application of second coat, at least 24 hours to dry completely
Container Sizes:	One-gallon or quart containers
Flammability:	Not flammable; water-based
Surface-Burning Characteristics:	Dry: ASTM E 84 Method Flame-Spread Index 0 Smoke Developed Index 0

All data and technical information are based on results achieved under typical application conditions. It is the customer's responsibility to verify if the product is suitable for the intended application. The responsibility for professional and correct installation and compliance with relevant building regulations lies with the customer. By ordering/receiving product you accept the **Armacell General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received these.

© Armacell, 2019. ArmaFlex is a trademark of the Armacell Group | WB Finish | ArmaFlex | TDS | 112019 | NA | EN-A | 082

ABOUT ARMACELL

As the inventors of flexible foam for equipment insulation and a leading provider of engineered foams, Armacell develops innovative and safe thermal, acoustic and mechanical solutions that create sustainable value for its customers. Armacell's products significantly contribute to global energy efficiency making a difference around the world every day. With 3,100 employees and 24 production plants in 16 countries, the company operates two main businesses, Advanced Insulation and Engineered Foams. Armacell focuses on insulation materials for technical equipment, high-performance foams for high-tech and lightweight applications and next generation aerogel blanket technology.

For more information:
www.armacell.us
info.us@armacell.com
800-866-5638

 **armacell**
ArmaFlex®